

# TREKKER4



## TREKKER4 F-M

4-085 • 4-095 • 4-105 • 4-110 • 4-120

*Landini*

Passion for Innovation.

	TREKKER 4-085 F/M	TREKKER 4-095 F/M	TREKKER 4-105 F/M	TREKKER 4-110 F/M	TREKKER 4-120 F/M
<b>ENGINE</b>					
Manufacturer	Deutz AG				
Model	TCD 2.9 L4 HT	TCD 2.9 L4 HP			
Max power (ISO)	hp/kW	75 / 55	90 / 66	95 / 70	102 / 75
Max torque	Nm	375	378	400	410
Displacement	cm³	2900			
Cylinders / Valves		4 TA / 8			
Emissions category		Stage V			
<b>CAPACITIES</b>					
Fuel tank	l	80			
<b>TRANSMISSION</b>					
Type		Speed Four			
No. of gears FWD+REV		● 16+8 Hi-Lo Overdrive - ○ 16+8 w/creeper			
Transmission control		Manually operated - 12" independent dry clutch			
Reverse shuttle		Mechanical synchro shuttle			
Transmission oil cooler		●			
<b>REAR PTO</b>					
Type		Servoassisted dry clutch			
Speeds	rpm	● 540 / 540 E - ○ 540 / 1000			
Rotation - spline shaft type		Clockwise (viewed from tractor rear) - ● 1-3/8" PTO shaft with 6 splines			
<b>STEERING AND BRAKING SYSTEM</b>					
Steering system		Hydrostatic Hi-Drive			
Steering control		2 independent levers with combined action on 2 wet clutches and on brakes			
Braking system		Hydrostatic wet multidisc graphite brakes			
<b>HYDRAULIC SYSTEM</b>					
Circuit type - pump type		Open centre - twin pump			
Flow rate hitch & remotes + steering	l/min	● 42 + 28 - ○ 56+28+28			
Max operating pressure	bar	180			
Rear remote valves		● 3 - ○ 4 / 5			
<b>REAR HYDRAULIC HITCH</b>					
Type		● mechanical - ○ mechanical with E.L.S. and position/draft/mixed/float control			
Category - coupler type		● Cat.2 - fixed ball ends - ○ Cat.2 - quick-hitch hooks			
Max lift capacity at hitch points	kg	● 3150 - ○ 4500 (w/assistor rams)			
<b>DRIVING POSITION</b>					
Cab type		○ 6-post high-visibility monocoque cab with opening rear window			
Cab suspension		suspended on hydro-silentblocks			
Cab air filter - filtration category		● dust filter Cat.2 and active carbon filter Cat.4			
Air conditioning		● manual A/C			
Radio system		● radio ready - ○ DAB radio and sound system			
Platform type		ROPS w/central tunnel w/side gears and reverse shuttle controls			
Platform suspension		Suspended on 4 Hydro Silent Block			
Lights		● Halogen driving and working lights - ○ LED driving and working lights			
Beacon light		○			
<b>ON-BOARD TECHNOLOGY</b>					
Digital dashboard		●			
<b>WEIGHTS AND DIMENSIONS</b>					
Wheelbase	mm	1650			
Ground clearance	mm	295			
Height over ROPS	mm	2400			
Max length without front weights	mm	3380			
Max overall width	mm	1410-1492 (F con soles in acciaio) / 1700-1750 (M)			
Shipping weight	kg	3900 (F) - 4500 (M)			
Front weight support		Built-in			
Front weights	kg	○ 6x30 / 8x30 / 8x30 + 33kg central front ballast			
<b>TRACKS</b>					
Bottom rollers		5			
Top carrier roller		Permanently lubricated			
Track tension adjustment system		Hydraulic track adjuster with permanently lubricated sprocket gear			
Front suspension		Leaf spring			
Rear suspension		Crossbar on independent track frames			
Track shoe type		● Metal - ○ Rubber			
Track shoe width	mm	310-360 (metal F) / 400-450 (metal M) / 450 (rubber M)			

Key: ● standard ○ option

All data and illustrations provided in this brochure are for information purposes only and can be changed without notice.

